


- SPACE QUALIFIED
- 200 - 1000 MHz
- BROADBAND, HIGH ISOLATION



TECHNICAL DESCRIPTION / APPLICATION


SERIES 03

The HJF-C-500 SQ Hybrid Junction covers 200 - 1000 MHz using a special lumped element design to reduce the size while maintaining high performance. This device has been designed in accordance with Merrimac document CENG-0001, "Standard Design Requirements for Space Qualified Devices".

GENERAL SPECIFICATIONS

MODEL NUMBER	FREQUENCY RANGE MHz	ISOLATION E-H (dB)		INSERTION LOSS dB		AMPLITUDE BALANCE dB		PHASE BALANCE		VSWR INPUT/ OUTPUT	
		MIN.	TYP.	MAX.	TYP.	MAX.	TYP.	MAX.	TYP.	MAX.	TYP.
HJF-C-500 SQ	200 - 1000	20	25	1.5	1.2	0.5	0.2	±7°	±5°	1.3:1	1.2:1
INPUT POWER MAX	COUPLING NOM.	IMPEDANCE NOM.		WEIGHT MAX.		OPERATING TEMPERATURE					
1 W	3.0 dB	50 OHM		5 g		-55° to +85 ° C					

PACKAGE OUTLINE



NOTES:

1. TOLERANCE ON 3 PLACE DECIMALS ±.020 (.51mm) EXCEPT AS NOTED.
2. DIMENSIONS = $\frac{\text{INCHES}}{[mm]}$
3. METRIC EQUIVALENTS ARE TO THE NEAREST .01mm.
4. WEIGHT: 5.0 GRAMS MAX.
5. PINS NOT MARKED ARE GROUND.

LABEL	1	E	2	H
H	0° REF	ISO	0°	
E	0° REF		-180	ISO